

PERFECTO GRANITO



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

PERFECTO GRANITE is a high decorative finish of exterior facades, highly weather-resistant, the aggression of different environments (marine, chemical). The finish is formulated with pure marble grains, enriched with precious silver or gold mica, this special synthesis leads to a result of great class, elegance and exclusivity. PERFECTO GRANITE can be applied to the most varied nature of the supports (concrete, lime, old plastic plasters, concrete, and so on)

• ADVANTAGES

High breathability (penetration rate of water vapour very close to that of the lime)

Very high water repellence (guarantee of water resistance)

- Self-cleaning (its microstructure surface, highly water-resistant, minimizes the contact area for water and dirt and helping self-cleaning)
- High elasticity (contains micro-movements of the substrate leaving its characteristics)
- Effect anticrack -(due to the excellent flexibility of the elastomer)
- Antialga-antifungal (essential in a thermal insulation to prevent the black algal)
- Excellent color resistance to ultraviolet and weather

Thanks to its characteristics PERFECTO GRANITO is used in buildings for the protection and decoration of wall surfaces both outside and inside of prestigious buildings, Villas Luxury Hotels, both new and old building, getting an excellent classic marble effect.

2. COMPOSITION

PERFECTO GRANITO is a paste product based elastomeric emulsion modified with siloxane resin, selected fillers, pigments resistant to light and weathering, specific additives.

3. METHOD OF APPLICATION

Mortar and lime or cement, paint or mineral and synthetic coatings, perfectly dry and cohesive are suitable, Apply a coat of SILOSSANA PRIMER diluted 100% with water; after 12 hours apply the first coat of PERFECTO LISCIO with a roller of the same colour as the finished one (diluted with about 5%water) covering

the surface actuarially. Depending on the colour chosen it may be necessary apply a third coat of PERFECTO LISCIO (diluted with about 5%water) After 24 hours spread a coat of PERFECTO GRANITO with a stainless steel trowel, when it is still humid create the final finish. Do not apply on surfaces where there is shown signs of rising damp or infiltration.

4. TECHNICAL DATA

SPECIFIC GRAVITY: 1,502 Kg./Lt. $\pm 5\%$

VISCOSITY' BROOKFIELD: cPS 12600 $\pm 20\%$ - R6 - RPM 20 - 25°C

PH: 8,43 ± 1

DRYING: dry to the touch: 4 hours at 20°C, with humidity less than 60% completely dry: 48 hours with humidity less than 60%

TEMPERATURE OF APPLICATION: between 5°C and 30°C

COVERAGE RATE: 2 kg/m².

COLOURS: to be chosen from our colour chart

PERMEABILITY TO WATER VAPOR: sd = 0.15 m (UNI 8202/43).

WATER ABSORPTION: W24 = 0.02 kg / m h0,5 (DIN 52013).

PACKAGE: Kg.20 polypropylene can

DILUTION : ready for use.

PRESERVATION: 24 months in the intact packages, away from temperature changes

HS-CODE: 32091000

5. ITEM OF SPECIFICATIONS

Decorative and protective plaster with encaustic effect, such as travertine effect PERFECTO GRANITO produced by Spiver Srl, elastomeric emulsion base modified with siloxane resin, selected aggregates, pigments resistant to light and weathering, specific additives; consolidating after treatment with a coat of PRIMER SILOSSANA of Spiver S.r.l. diluted with 100%, and 2 coats of PERFECTO LISCIO diluted with 10% water, of the colours chosen from the P.M..

Price inclusive of the material and implementation, without the scaffoldings per square metre: €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company's control and on the agents unrelated to the product quality.



Emotion with paint ...

SPIVER s.r.l.

contradaBabbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it

Scheda Tecnica: PERFECTO GRANITO SP 109. Rev.1 La presente scheda annulla e sostituisce le precedenti