

PERFECTO LISCIO



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Wall paint especially suitable for external b resins based. The name PERFECTO LISCIO derives from the fact that fulfilling all the requirements for perfect protection and decoration of external wall finishes in the new construction and restoration.

ADVANTAGES

- High breath ability (index of permeability to water vapour very close to that of lime)
- Peak waterproof (guarantee of protection from water)
- Self (his microstructure surface, highly water repellent, minimizes the surface of contact for water and dirt and promotes the slip)
- High elasticity (contains the micro substrate leaving unchanged its characteristics)
- Effect anti crepe- (due to excellent flexibility from the wall)
- Anti fungicide (fundamental coatings to coat to prevent algal)
- Excellent keeping colours to U.V. and the weather.

Thanks to its characteristics PERFECTO LISCIO can be employed in construction for the protection and decoration of wall surfaces both external and internal buildings new and old construction, on media is that synthetic mineral nature (or mixed in some restorations) and in particular coatings to coat where they will be perfect protection.

2. COMPOSITION

PERFECTO LISCIO is a paste-based emulsion modified with resin silossanica product, pigments resistant to light and to weather conditions and with special additives.

3. METHODS OF APPLICATION

Lime based or cement mortar or painted, mineral or synthetic, perfectly dry and cohesive. Apply a coat of SILOSSANA PRIMER diluted to 50% with water, after 12 hours apply a coat as a base PERFECTO LISCIO diluted with 40% of water of the chosen colours, after 12 hours apply the second coat of PERFECTO LISCIO diluted max 20 %. Do not apply on surfaces where there is presence of moisture lifts or infiltration.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 1,500 Kg./Lt. +/- 0,5%

ASPETTO FILM: not shiny

VISCOSITY: tixotropica paste

DRYING: TO TOUCH: ABOUT: 4 hours 20°C

COMPLETLY DRY: about 48 hours a 20°C

APPLICATION TEMPERATURE: BETWEEN 5°C e 30°C

YIELD: 2,8 – 3,5 mq/Lt.

WATER RESISTANCE: sd = 0,15 m (UNI 8202/43)

WATER ABSORBMENT: W24 = 0,02 Kg/m h0,5 (DIN 52013)

COLOURS: SHADES FROM OUR COLOUR CHART

PACKAGING: PLASTIC CANS OF Lt.14

APPLICATION: BRUSH, ROLLER, SPRAY

DILUTION: 20-40 % with water for the application with a brush or roller.

PRESERVATION: 24 months in the intact packages, away from temperature changes

HS-CODE: 32091000

5. ITEM OF SPECIFICATIONS

Decorating and protection of external surfaces with paint such as the type of PERFECTO LISCIO Spiver Inc. , emulsion based modified with resin silossanica, pigments resistant to light and to weather conditions, special additives; consolidating after treatment with a coat of SILOSSANA PRIMER of Spiver Inc. diluted with 50% water, followed by applying a coat of PERFECTO LISCIO diluted with 40% water, the second of PERFECTO LISCIO diluted with 20% of water dyed chosen by DL

The price includes the equipment and implementation, excluding the scaffolding sqm. €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality



Emotion with paint ...

SPIVER s.r.l.

contradaBabbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it