



PERFECTO SIENA



1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Outdoor wall finish fibre reinforced ,resins base. PERFECTO The name derives from the fact that fulfilling all the requirements for perfect protection and decoration of external facades in the new construction and restoration.

ADVANTAGES

- High breath ability (index of permeability to water vapour very close to that of lime)
- Peak waterproof (guarantee of protection from water)
- Self (his microstructure surface, highly water repellent, minimizes the surface of contact for water and dirt and it encourages it to fall of easily)
- High elasticity (contains the micro substrate leaving unchanged its characteristics)
- Effect ant crêpe- (due to the of fibre producing an excellent three-dimensional and excellent flexibility)
- Ant- fungicide (fundamental coatings to coat to prevent algal)
- Excellent keeping colours to U.V. and the weather.

Thanks to its characteristics PERFECTO SIENA can be employed in construction for the protection and decoration of wall surfaces both external and internal buildings new and old construction, on media is that synthetic mineral nature(or mixed in some restorations) and in particular coatings to coat where they will be perfect protection.

2.COMPOSITION

PERFECTO SIENA is a paste-based emulsion modified with resin silasonic product, pigments resistant to light and to weather conditions and with special additives.

3.METHODS OF APPLICATION

Lime based or cement mortar or painted, mineral or synthetic, perfectly dry and cohesive. Apply a coat of SILOSSANA PRIMER diluted to 50% with water, after 12 hours apply a coat as a base PERFECTO LISCIO diluted with 40% of water of the chosen colours. Spread a coat of PERFECTO SIENA with stainless steal float and finish it with a plastic trowel. Do not apply on surfaces where there is presence of moisture lifts or infiltration.

4. TECHNICAL DATA

SPECIFIC WEIGHT: 18540 Kg./Lt. +/- 0,5%

VISCOSITY: tixotropica paste

DRYING TO TOUCH: ABOUT 4 hours 20°C

COMPLET DRY: about 48 hours a 20°C

APPLICATION TEMPERATURE: BETWEEN 5°C e 30°C

YIELD: ROUGH BIG ((1,5mm) 2,8 - 3 kg./mq.; FINER SMALL (1mm) 2,2 – 2,5 kg./mq.

WATER RESISTANCE: 0,15 m (UNI 8202/43)

WATER ABSORBMENT W24: 0,02 Kg/m h0,5 (DIN 52013)

COLOURS: SHADES FROM OUR COLOUR CHART

PACKAGING: PLASTIC CANS OF 25 KG

DILUTION: READY TO USE

PRESERVATION: 24 months in the intact packages, away from temperature changes

HS-CODE: 32091000

5.ITEM OF SPECIFICATIONS

Decorating and protection of external surfaces with paint such as the type of PERFECTO SIENA Spiver Inc. , emulsion based modified with resin silossanica, , pigments resistant to light and to weather conditions, special additives; consolidating after treatment with a coat of SILOSSANA PRIMER of Spiver Inc. diluted with 50% water, followed by applying a coat of PERFECTO LISCIO diluted with 40% water, the second of PERFECTO LISCIO diluted with 20% of water dyed chosen by DL

The price includes the equipment and implementation, excluding the scaffolding sqm. €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality



Emotion with paint ...

SPIVER s.r.l.

contradaBabbaurra S.S. 122

93100 Caltanissetta (CL)

Tel. +39 0934 57 77 91 Fax +39 0934 58 87 95

www.spiver.it - info@spiver.it